

TheaterTouch™

RTI



REMOTE TECHNOLOGIES INCORPORATED



## The Power Of A Touchscreen In The Palm Of Your Hand

### A Better Design

The amazing TheaterTouch universal system controller combines the power and flexibility of a graphic LCD touch screen with an ergonomic design that permits effortless one-handed operation. This design overcomes the need for compromise between form and function. Sleek and perfectly balanced, TheaterTouch is also infinitely flexible and expandable.

TheaterTouch takes complete control of the home theater, replacing all other remotes. It features an intuitive, easy-to-read LCD that can display custom buttons, text and graphics. In

addition to the backlit display, there are 25 hard buttons that allow easy access to frequently used functions.

Programming is easy and convenient thanks to the built-in infrared learning ability and the Windows® based software.

### Unique Features

TheaterTouch is capable of both infrared and radio frequency output. A separate RF to IR converter is available for transmission through walls and cabinets. The converter will also monitor the power status of most A/V equipment. Additional features include:

- A tilt sensor that can turn on the display when the unit is picked up
- A programmable beeper to indicate when a button is pressed
- Any button can be programmed to transmit multiple commands
- Programmable display time-out values and backlight settings

### Customer Support

TheaterTouch is covered by a one-year warranty. General information and technical support can be obtained by calling RTI at 952-253-3100, or by e-mail using the RTI Web site at [www.theatertouch.com](http://www.theatertouch.com).

*TheaterTouch uses detachable, low profile NiMH battery packs that permit a slim, light-weight design.*

*TheaterTouch includes a powerful Windows® Software package for programming.*

### SPECIFICATIONS

<b>POWER:</b>	4.8 Volt NiMH Rechargeable Battery
<b>INFRARED CONTROL RANGE:</b>	30 Feet (9.1m) @ 60 Degrees
<b>INFRARED CARRIER FREQUENCY RANGE:</b>	15KHz-455KHz
<b>RADIO FREQUENCY CONTROL RANGE:</b>	Up to 100 Feet (30.5m)
<b>RADIO FREQUENCY CARRIER :</b>	418 MHz
<b>DISPLAY:</b>	128 x 64 pixels STN (Blue on White)
<b>BACKLIGHT:</b>	White EL (Display) Blue EL (Keypad)
<b>NOMINAL RUN TIME ON FULL CHARGE:</b>	6.5 Hours Minimum
<b>SYSTEM MEMORY:</b>	128K Bytes Flash (non-volatile) Memory
<b>COMMUNICATIONS:</b>	RS-232 Serial Port
<b>DIMENSIONS:</b>	9.9" x 2.4" x 1.1" (251mm x 61mm x 28mm)
<b>WEIGHT:</b>	10 oz. (283g)

*All specifications subject to change without notice*

